

Heavy Duty Spindle for Ring Doublers / Ring twister





Products Spindles: HZ- 3C, HZ-44,

For Machine:

, ISHIKAWA , , AAWADHKRUPA , LAXMI NARAYAN INDUSTRIES (LNI), JMW , HAZUR MAKINA , MINARVA, BIRKO AS , GIESSE , MILHAN MAKINA, HUZUR MAKINA ETC ...

For Process Type: cotton industries, fiber glass industries, nylon fish net twine industries, jute industries, asbestos industries etc.....

Product Description

- Material: spindle blade: EN 31 (bearing steel), aluminum plug: LM 6, wharves: EN 24
- Spindle's wharves diameter 24.5 mm to above
- high quality, low vibration, long life
- supplies complete set with flange, nut, spindle lock
- manufacture spindle for ring diameter: 3.5 " and 4 "
- we supplied spindle with specified insert as Texparts, Jaylaxmi.







Spindle Application

- Jaylaxmi reduce vibration up to 0.05 mm / sec
- Lift size 204 to 420 mm
- Jaylaxmi reduce noise to 75 DBA
- Long life
- We can reduce the weight of spindle top part (new design)
- Short delivery time

Advantages

- Low noise & Power
- High speed up-to 8000 rpm.
- Dynamically balanced.
- 6 Stage Quality Checks to ensure exquisite quality system maintenance for superior performance.
- Made to fit your system and give higher and better performance index.

> Technical Data Sheet

Type of Spindle	Wharves dia. (mm)	LIFT size (mm)	Insert / bolster		Speed- RPM(Mechanical)	Weight in kgs (S.U.P)
Ring doublers	25.4 mm and above	204 to 420	Jaylaxmi / TEXPART		3,000 to 12,000	0.525 and above



